

New! 1QL CHOICE QUARTER ROUND EXTRUSION - LENSED


1QL Choice: IP40 | Quarter Round extrusion fits snugly into corners for bright, even linear lighting. UL Listed dry/damp. Includes selection of 3 LED Boards with EssentialLEDs Choice LEDs on a Narrow Pitch. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. Choice of Clear Acrylic lens (standard), or 3 Opal diffusion lenses. Photometrics vary based on CCT and lensing; see vltcorp.com for output conversion and other data specific to your fixture choices.

AVAILABLE IN LENGTHS UP TO 95.28" [2420MM]




(Beam Angle based on 1QL fixture with Clear Acrylic lens)



ELC-1QL -


LED		Finish		Wire Exit ²		Listings	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI	AL	Silver Anodized	C	Custom	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI	BL	Black Anodized	² Because of 1QL's asymmetric form, special care should be taken when specifying Wire Exit.		CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI						
Narrow Pitch Choice LEDs		CCT		Lens Options		Fixture Length See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]	
	23	2300°K	PG	Clear Acrylic			
	27	2700°K	OP1	Opal 1, Frosted			
	30	3000°K	OP2	Opal 2, Medium			
	35	3500°K	OP3	Opal 3, Heavy ¹			
	40	4000°K			¹ Not Title 24 JA8-2016 compliant		

1QL tucked behind lighting valance



1QL's self-contained mounting flange allows the fixture to fit tightly into corners, with a 94° beam angle and wide field angle for fully lighting shelf and undercabinet spaces. 1QL can tuck neatly behind a lighting valance, as illustrated at left, or if no valance is provided, 1QL can mount flush with the front edge of the shelf or cabinet. The fixture's slim, finished back surface ensures an attractive presentation, as shown in the photos to the right.

The 1QL flange is scored for easy drilling; mounting holes should be drilled approximately every 20" (minimum two holes per fixture). The 1QL fixture can also be mounted using VHB tape.



1QL mounted on shelf edge



When visible, the slim 1QL fixture adds an attractive accent to cabinetry

