

**New!** 1R CHOICE SMALL ROUND EXTRUSION - NO LENS


1R Choice: IP20 | Round extrusion for linear lighting applications. Includes selection of 3 LED Boards with EssentialLEDs Choice LEDs on a Narrow Pitch. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. No lens. Refer to Mounting Options for other possible choices. Photometrics vary based on CCT; see vltcorp.com for output conversion and other data specific to your fixture choices.

AVAILABLE IN LENGTHS UP TO 95.28" [2420MM]



OBSERVE PRECAUTIONS FOR HANDLING ELECTROSTATIC SENSITIVE DEVICES



ELC- 1R -

LED		Finish		Wire Exit		Listings & Options <sup>1</sup>	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI	AL	Silver Anodized	WE1	Default	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI	BL	Black Anodized	C	Custom	CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI	C	Custom			IM	Inside Mount End Caps <sup>1</sup>

CCT		Lens Options		Fixture Length	
23	2300°K	NL	No Lens	See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]	
27	2700°K				
30	3000°K				
35	3500°K				
40	4000°K				

Listings & Options <sup>1</sup>	
EM8	8mm End Mount Leg <sup>1</sup>
TM8	8mm T-Mount Leg <sup>1</sup>
CM8	8mm Corner Mount Leg <sup>1</sup>
BU	Bushing <sup>1</sup>

<sup>1</sup> Finish on Factory Installed Options will match specified finish; see Mounting Options.

See Special Mounting Options for more information about specifying 1R fixtures in Display Case

Basic Fixture Accessories - See Mounting Options For Full Options

ELL - AC - 1R - PC	ELL - AC - 1R - LC	ELL - AC - 1R - SALC	ELL - AC - 1R - MRC
<b>Plastic Mounting Clip;</b> extrusion rotates into clip. Extrusion sits 1/16" (1.59mm) off mounting surface. See Mounting Options.	<b>Locking Adjustable Mounting Clip;</b> use one at each end of extrusion, alone or with Plastic Clips; 4-40 set screws lock extrusion at desired angle. Extrusion sits 1/16" (1.59mm) off mounting surface. See Mounting Options.	<b>Locking Adjustable Self-Adhesive Clip;</b> use alone or with Plastic Clips; attaches with VHB tape; 4-40 set screws lock extrusion at desired angle. Extrusion sits 1/16" (1.59mm) off mounting surface. See Mounting Options.	<b>Metal Mounting Clip;</b> Fixture extrusion rotates into clip. Countersunk screw-hole so fixture sits flush to mounting surface. Allows 60° rotation. Allow 1 per 12" (min. 2 per fixture); Polished Nickel Finish; See Mounting Options.