


1R SMALL ROUND EXTRUSION - NO LENS

1R: IP20 | Round extrusion for linear lighting applications. Includes Nichia LEDs in choice of 11 LED Board options. See lumen outputs, CCTs, wattage and other variables on Linear Fundamentals.

Available in Silver, Black or Bronze Anodized, White Powder Coated, or Custom Finishes. No lens. Photometrics vary based on CCT; see vltcorp.com for output conversion and other data specific to your fixture choices.



OBSERVE PRECAUTIONS FOR HANDLING ELECTROSTATIC SENSITIVE DEVICES



ELL- 1R -

LED		CCT		Finish		Lens Options		Wire Exit		Listings & Options	
1720	260 lm/ft, 1.8 w/ft, 83 CRI	20	2000°K	AL	Silver Anodized	NL	No Lens	WE1	Default	UL	UL Listed
2730	397 lm/ft, 2.9 w/ft, 83 CRI	22	2200°K	BL	Black Anodized			C	Custom	CE	CE Marked (RoHS)
4740	528 lm/ft, 3.7 w/ft, 83 CRI	25	2500°K	BZ	Bronze Anodized					IM	Inside Mount End Caps <sup>2</sup>
5760	665 lm/ft, 4.9w/ft, 83CRI	27	2700°K	WH	White Powder Coat					EM8	8mm End Mount Leg <sup>2</sup>
6760	875 lm/ft, 6.5w/ft, 83 CRI	30	3000°K	C	Custom					TM8	8mm T-Mount Leg <sup>2</sup>
3720	223 lm/ft, 1.8 w/ft, 95 CRI	35	3500°K							CM8	8mm Corner Mount Leg <sup>2</sup>
3740	430 lm/ft, 3.5 w/ft, 95 CRI	40	4000°K							BU	Bushing <sup>2</sup>
3760	609 lm/ft, 5.2 w/ft, 95 CRI	45	4500°K								
3790	621 lm/ft, 6.9 w/ft, 98 CRI <sup>1</sup>	50	5000°K								
5133	315 lm/ft, 3.4 w/ft, 87 CRI <sup>1</sup>										
5163	548 lm/ft, 6.6 w/ft, 87 CRI <sup>1</sup>										

**Fixture Length**  
See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]

<sup>2</sup> Finish on Factory Installed Options will match specified finish; see Mounting Options page.

Standard HI CRI Pitchless Ultra HI CRI

<sup>1</sup>Not Available in 20K, 22K or 25K CCT

See Special Mounting Options for more information about specifying 1R fixtures in Display Case

Basic Fixture Accessories - See Mounting Options for more information

ELL - AC - 1R - PC	ELL - AC - 1R - LC	ELL - AC - 1R - SALC	ELL - AC - 1R - MRC
<b>Plastic Mounting Clip;</b> extrusion rotates into clip. Extrusion sits 1/16" (1.59mm) off mounting surface. See Mounting Options.	<b>Locking Adjustable Mounting Clip;</b> use one at each end of extrusion, alone or with Plastic Clips; 4-40 set screws lock extrusion at desired angle. Extrusion sits 1/16" (1.59mm) off mounting surface. See Mounting Options.	<b>Locking Adjustable Self-Adhesive Clip;</b> use alone or with Plastic Clips; attaches with VHB tape; 4-40 set screws lock extrusion at desired angle. Extrusion sits 1/16" (1.59mm) off mounting surface. See Mounting Options.	<b>Metal Mounting Clip;</b> Fixture extrusion rotates into clip. Countersunk screw-hole so fixture sits flush to mounting surface. Allows 60° rotation. Allow 1 per 12" (min. 2 per fixture); Polished Nickel Finish.