

# Fiber Optic Illuminator - 20 Watt LED




PORT	Available with 28mm port to hold up to 800 - 0.75mm fibers at standard brightness, or with 9mm port to hold up to 140 - 0.75mm fibers at standard brightness.		
CONTROL	Available in White Light or with optional Permanent Color. Dimmable. Continuous ColorWheel, TwinkleWheel (optional).		
LAMP	Nichia or CREE LEDs		
ELECTRICAL	Electrical transformer; 120-240v/50-60Hz; 6' attached power cord with connector; 0.6amps. continuous load at 120 volts		
ENCLOSURE	IP20 rating for dry or damp operating environment; anodized aluminum housing; Synjet forcedair cooled; 7 dB(A) quiet fan; weight 1 kilograms (2.2 lbs.)		
FIBER CAPAC-	28mm port: 1000 - 0.75mm; 9mm port: 140 - 0.75mm; accepts stranded PMMA or glass		
HARNESS	28mm, 9mm		
MOUNTING AND VENTILATION	3" all sides recommended clearance; -10°C min/+45°C		
LISTINGS	ETL, CE, and cUL listed		
DIMMING	0-10v		


### **Features:**

- Compact size ideal for display cases
- Extremely quiet fan
- Full range dimming 0-10v

### **MOUNTING GUIDE**




### **AIRFLOW GUIDE**



## FIBER OPTIC LIGHTING

## Fiber Optic Illuminator - 20 Watt LED



#### Modifiers & Accessories

4900 0115	Permanent Filter Bracket Only	TWA	Twinkle Wheel Adapter Kit (refer to Illuminator Accessory Sheet)
PC	Permanent Color Filter (refer to Illuminator Accessory Sheet)	CWA	Color Wheel Adapter Kit (refer to Illuminator Accessory Sheet)
CW/E	Extended Palette Color Wheel (refer to Permanent Color Sheet)		
CW/C	Custom Color Wheel (specify any colors, may require long lead time)		
TW/B	Twinkle Wheel with Bars (refer to Illuminator Accessory Sheet)		
TW/SS	Twinkle Wheel for Shooting Star (refer to Illuminator Accessory Sheet)		
TW/CW	Twinkle/Color Wheel (refer to Custom Color Sheet)		
TW/CD	Twinkle/Color Wheel w/Crushed Dichroics (refer to Custom Color Sheet)		