


## New! 2RL CHOICE LARGE ROUND EXTRUSION - LENSED

2RL Choice: IP40 | Round extrusion for linear lighting applications. UL Listed dry/damp. Includes selection of 3 LED Boards with EssentialLEDs Choice LEDs on a Narrow Pitch. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. Choice of Clear Acrylic lens (standard), or 3 Opal diffusion lenses. Refer to Mounting Options for other possible choices. Photometrics vary based on CCT and lensing; see vltcorp.com for output conversion and other data specific to your fixture choices.



(Beam Angle based on 2RL fixture with Clear Acrylic lens)



AVAILABLE IN LENGTHS UP TO 95.28" [2420MM]

ELC-2RL -

LED		Finish		Wire Exit		Listings & Options	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI	AL	Silver Anodized	WE1	Default	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI	BL	Black Anodized	C	Custom	CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI					IM	Inside Mount End Caps <sup>1</sup>
Narrow Pitch Choice LEDs						EM8	8mm End Mount Leg <sup>1</sup>
						TM8	8mm T-Mount Leg <sup>1</sup>
						CM8	8mm Corner Mount Leg <sup>1</sup>
						EM16	16mm End Mount Leg <sup>1</sup>
						TM16	16mm T-Mount Leg <sup>1</sup>
						CM16	16mm Corner Mount Leg <sup>1</sup>
						BU	Bushing <sup>1</sup>

CCT

23	2300°K
27	2700°K
30	3000°K
35	3500°K
40	4000°K

Lens Options

PG	Clear Acrylic
OP1	Opal 1, Frosted
OP2	Opal 2, Medium
OP3	Opal 3, Heavy <sup>1</sup>

<sup>1</sup> Not Title 24 JA8-2016

Fixture Length

See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C (311mm)

<sup>1</sup> Finish on Factory Installed Options will match specified finish; see Mounting Options.

See Special Mounting Options for more information about specifying 2RL fixtures in Display Case

### Basic and Free Standing Fixture Accessories - See Mounting Options For Full Options

ELL - AC - 2RL - PC	ELL - AC - 2RL - LC	ELL - AC - 2RL - SALC	ELL - AC - 2RL - MRC
<b>Plastic Mounting Clip;</b> Fixture extrusion rotates into clip. Screws to mounting surface. Raises fixture 0.13" (3.18mm). Allows 30° rotation. Allow 1 per 12" (min. 2 per fixture); See Mounting Options.	<b>Locking Adjustable Mounting Clip;</b> Screws to mounting surface. Raises fixture 0.13" (3.18mm). Full rotation with locking screw. Finishes to match fixture. Allow 2 per fixture (48" max span). See Mounting Options.	<b>Locking Adjustable Mounting Clip with Self-Adhesive.</b> Raises fixture 0.13" (3.18mm). Full rotation with locking screw. Finishes to match fixture. Allow 2 per fixture (48" max span). See Mounting Options.	<b>Metal Mounting Clip;</b> Fixture extrusion rotates into clip. Countersunk screw-hole so fixture sits flush to mounting surface. Allows 60° rotation. Allow 1 per 12" (min. 2 per fixture); Polished Nickel Finish; See Mounting Options.