


2RL LARGE ROUND EXTRUSION - LENSED

2RL: IP40 | Round extrusion for linear lighting applications. UL Listed dry/damp. Includes Nichia LEDs in choice of 11 LED Board options. See lumen outputs, CCTs, wattage and other variables on Linear Fundamentals.

Available in Silver, Black or Bronze Anodized, White Powder Coated, or Custom Finishes. Choice of Clear Acrylic lens (standard), 3 Opal diffusion lenses, or four focusing lenses L2 (18° - 31°), L3 (30° - 42°) or Lens 4 (78° - 82°). Photometrics vary based on CCT and lensing; see vltcorp.com for output conversion and other data specific to your fixture choices.



(Beam Angle based on 2RL fixture with Clear Acrylic lens)



ELL- 2RL -

LED		CCT		Finish		Lens Options ²		Wire Exit		Listings & Options	
1720	260 lm/ft, 1.8 w/ft, 83 CRI	20	2000°K	AL	Silver Anodized	PG	Clear Acrylic	WE1	Default	UL	UL Listed
2730	397 lm/ft, 2.9 w/ft, 83 CRI	22	2200°K	BL	Black Anodized	L2	Lens 2 (18° - 31°)	C	Custom	CE	CE Marked (RoHS)
4740	528 lm/ft, 3.7 w/ft, 83 CRI	25	2500°K	BZ	Bronze Anodized	L3	Lens 3 (30° - 48°)	Fixture Length See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]		IM	Inside Mount End Caps ³
5760	665 lm/ft, 4.9w/ft, 83CRI	27	2700°K	WH	White Powder Coat	L4	Lens 4 (78° - 82°)			EM8	8mm End Mount Leg ³
6760	875 lm/ft, 6.5w/ft, 83 CRI	30	3000°K	C	Custom	OP1	Opal 1, Frosted	TM8	8mm T-Mount Leg ³	CM8	8mm Corner Mount Leg ³
3720	223 lm/ft, 1.8 w/ft, 95 CRI	35	3500°K			OP2	Opal 2, Medium	EM16	16mm End Mount Leg ³	TM16	16mm T-Mount Leg ³
3740	430 lm/ft, 3.5 w/ft, 95 CRI	40	4000°K			OP3	Opal 3, Heavy	CM16	16mm Corner Mount Leg ³	BU	Bushing ³
3760	609 lm/ft, 5.2 w/ft, 95 CRI	45	4500°K								
3790	621 lm/ft, 6.9 w/ft, 98 CRI ¹	50	5000°K								
5133	315 lm/ft, 3.4w/ft, 87 CRI ¹										
5163	548 lm/ft, 6.6w/ft, 87 CRI ¹										

² See Lensing Options for more information on L2, L3 & L4 optical lenses

³ Finish on Factory Installed Options will match specified finish; see Mounting Options page.

■ Standard
 ■ HI CRI
 ■ Ultra HI CRI
 ■ Pitchless

¹ Not Available in 20K, 22K or 25K CCT

See Special Mounting Options for more information about specifying 2RL fixtures in Display Case

Basic and Free Standing Fixture Accessories - See Mounting Options for more information

ELL - AC - 2RL - PC	ELL - AC - 2RL - LC	ELL - AC - 2RL -SALC	ELL - AC - 2RL - MRC
Plastic Mounting Clip; Fixture extrusion rotates into clip. Screws to mounting surface. Raises fixture 0.13" (3.18mm). Allows 30° rotation. Allow 1 per 12" (min. 2 per fixture); See Mounting Options.	Locking Adjustable Mounting Clip; Screws to mounting surface. Raises fixture 0.13" (3.18mm). Full rotation with locking screw. Finishes to match fixture. Allow 2 per fixture (48" max span). See Mounting Options.	Locking Adjustable Mounting Clip with Self-Adhesive. Raises fixture 0.13" (3.18mm). Full rotation with locking screw. Finishes to match fixture. Allow 2 per fixture (48" max span). See Mounting Options.	Metal Mounting Clip; Fixture extrusion rotates into clip. Countersunk screw-hole so fixture sits flush to mounting surface. Allows 60° rotation. Allow 1 per 12" (min. 2 per fixture); Polished Nickel Finish; See Mounting Options.