












VLT MULTI-DIM ELECTRONIC LINEAR DRIVERS, 5N1 DIMMING

VLT Electronic Dimming Class 2 LED Drivers is compatible with MLV, ELV, Triac, 0-10v or PWM Dimmers, providing flicker-free 0.1% dimming. VLT 5n1 drivers feature solid state circuits with Auto reset breakers from short circuit, overloading, and over temperature conditions. UL Listed for Indoor or Outdoor use (UL1013 & UL8750)

30W 24DC	SPECIFICATIONS	CAT NO.: HELD-5N1-30-24DC-UNV
 <p>(Custom white shown. Black standard.)</p> 	<p>Load: 1-30 VA Input Voltage: 120-277V AC Output Voltage: 24v DC ±1% Dimensions: 6.50" L x 3.72" W x 1.57" H [165mm x 94.5mm x 40mm] Circuits: 1 Frequency: 50/60Hz Weight: 2.0 lbs (0.9 kg) Max Ambient Temp.: 140° F [60° C] IP Rating: IP66 Listings: UL Listed (UL1310, UL 8750) Manufacturer: Visual Lighting Technologies</p>	<p>Description: Constant voltage driver from VLT, 30W, 1.25A; 5 in 1 dimmable driver, MLV, ELV, Triac, 0-10v, PWM Dimmers; Flicker Free 0.1% Dimming, Universal Input 120v – 277v; 24v DC Output, Class 2. Conduit access wiring compartment for wall mounting, UL listed for indoor or outdoor use.</p> 
 <p>(Custom white shown. Black standard.)</p> 	<p>Load: 1-60 VA Input Voltage: 120-277V AC Output Voltage: 24v DC ±1% Dimensions: 7.4" L x 3.72" W x 1.57" H [188mm x 94.5mm x 40mm] Circuits: 1 Frequency: 50/60Hz Weight: 2.4 lbs (1.1 kg) Max Ambient Temp.: 140° F [60° C] IP Rating: IP66 Listings: UL Listed (UL1310, UL 8750) Manufacturer: Visual Lighting Technologies</p>	<p>Description: Constant voltage driver from VLT, 60W, 2.5A; 5 in 1 dimmable driver, MLV, ELV, Triac, 0-10v, PWM Dimmers; Flicker Free 0.1% Dimming, Universal Input 120v – 277v; 24v DC Output, Class 2. Conduit access wiring compartment for wall mounting, UL listed for indoor or outdoor use.</p> 
 <p>(Custom white shown. Black standard.)</p> 	<p>Load: 1-96 VA Input Voltage: 120-277V AC Output Voltage: 24v DC ±1% Dimensions: 8.66" L x 3.72" W x 1.57" H [220mm x 94.5mm x 40mm] Circuits: 1 Frequency: 50/60Hz Weight: 2.80 lbs (1.3 kg) Max Ambient Temp.: 140° F [60° C] IP Rating: IP66 Listings: UL Listed (UL1012, UL1310), Manufacturer: Visual Lighting Technologies</p>	<p>Description: Constant voltage driver from VLT, 96W, 4A; 5 in 1 dimmable driver, MLV, ELV, Triac, 0-10v, PWM Dimmers; Flicker Free 0.1% Dimming, Universal Input 120v – 277v; 24v DC Output, Class 2. Conduit access wiring compartment for wall mounting, UL listed for indoor or outdoor use.</p> 
 <p>(Custom white shown. Black standard.)</p> 	<p>Load: 1-96 VA (3 circuits) Input Voltage: 120-277V AC Output Voltage: 24v DC ±1% Dimensions: 11.85" L x 4.32" W x 1.81" H [301mm x 110mm x 45mm] Circuits: 3 Frequency: 50/60Hz Weight: 5.20 lbs (2.4 kg) Max Ambient Temp.: 140° F [60° C] IP Rating: IP66 Listings: UL Listed (UL1012, UL1310), Manufacturer: Visual Lighting Technologies</p>	<p>Description: Constant voltage driver from VLT, 288W, 96w x 3 outputs, 4A each; 5 in 1 dimmable driver, MLV, ELV, Triac, 0-10v, PWM Dimmers; Flicker Free 0.1% Dimming, Universal Input 120v – 277v; 24v DC Output, Class 2. Conduit access wiring compartment for wall mounting, UL listed for indoor or outdoor use.</p> 