


New! 5SLW CHOICE SQUARE EXTRUSION - EXTERIOR

5SLW Choice: UL Listed for Wet Locations | Square extrusion suitable for wet location linear lighting applications, both indoors and outdoors.¹ Includes selection of 3 LED Boards with EssentialLEDs Choice LEDs on a Narrow Pitch. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. Photometrics vary based on CCT and lensing; see vltcorp.com for conversion and other data specific to your fixture choices.

¹ A wet location is an interior or exterior location in which water or other liquids may drip, splash or flow on or against the electrical components of a lighting fixture

AVAILABLE IN LENGTHS UP TO 72.29" [1836MM]



(Beam Angle based on 5SLW fixture with Clear Acrylic lens)


ELC- 5SLW -

LED		Finish		Wire Exit		Listings	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI	AL	Silver Powder Coat	WE1R	4' Bare End	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI	BL	Black Powder Coat			CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI						

CCT		Lens Options		Fixture Length	
23	2300°K	PG	Clear Acrylic	See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice.	
27	2700°K	OP1	Opal 1, Frosted		
30	3000°K				
35	3500°K				
40	4000°K				

Narrow Pitch Choice LEDs

FIXED CLIP SPECIFICATIONS CAT. NO. ELL-AC-5SLW-MC



Dimensions: 0.88" [22.28mm] x 0.60" [15.29mm]
Material: 301 Stainless Steel

Description: Fixed Metal Clip for mounting 5SLW square extrusion. Screws to mounting surface with screw, provided. Fixture extrusion snaps into clip. Allow 1 per 20" of extrusion (min. 2 per fixture).