

EssentialLEDs®


CHOICE

7SL CHOICE SMALL SQUARE EXTRUSION - EDGE TO EDGE

7SL Choice: IP54 | Small square extrusion for linear lighting applications. Slim extrusion wall (0.15") and edge-to-edge snap-in lensing for extra lumen output. UL Listed dry/damp. Includes selection of 3 LED Boards with EssentialLEDs Choice LEDs on a Narrow Pitch. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. Choice of Clear Acrylic lens (standard), 3 Opal diffusion lenses, or two focusing lenses L3 (50° - 51°) or L4 (89° - 92°).

AVAILABLE IN LENGTHS UP TO 143.3" [3640MM]



ELC- 7SL -

LED		Finish		Wire Exit		Listings & Options	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI	AL	Silver Anodized	WE1	Default	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI	BL	Black Anodized	C	Custom	CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI					MAG	Magnetic Mount

Narrow Pitch Choice LEDs

CCT	
23	2300°K
27	2700°K
30	3000°K
35	3500°K
40	4000°K

Lens Options	
PG	Clear Acrylic
L3	Lens 3 (50° - 51°)
L4	Lens 4 (89° - 92°)
OP1	Opal 1, Frosted
OP2	Opal 2, Medium ¹
OP3	Opal 3, Heavy ^{1,2}

Fixture Length
See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows:
C (12.25") or C [311mm]

¹ Will provide full diffusion
² Not Title 24 JA8-2016 compliant

Fixture Accessories

ELL - AC - 7SL - MC	ELL - AC - 7SL - AMC	ELL - AC - S123 - AB	Factory Installed; See Options Above
Fixed Metal Mounting Clip. Fixture extrusion snaps into clip. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	Adjustable Metal Mounting Clip. Offset screws allow flush mounting. Bends to desired angle. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	Adjustable Metal Bracket for use with Fixed Metal Mounting Clip (one bracket per clip). 30° adjustability. Raises fixture 3/8" (9.52mm). Bracket allows repeated angle adjustments, and easier angle adjustments in hard-to-reach areas like ceiling coves. See Mounting Options.	Magnetic Mount Small, strong, factory installed magnets recess into rear side of fixture extrusions for mounting of fixture onto suitable ferrous surface or accessory Steel Mounting Plates; 3 magnets per foot. Magnets protrude 0.08" [2.1mm] above rear surface of extrusion.