


## 7SL SMALL SQUARE EXTRUSION - EDGE TO EDGE LENS

7SL: IP54 | Small square extrusion for linear lighting applications. Slim extrusion wall (0.15") and edge-to-edge snap-in lensing for extra lumen output. UL Listed dry/damp. Includes Nichia LEDs in choice of 11 LED Board options. See lumen outputs, CCTs, wattage and other variables on Linear Fundamentals.

Available in Silver, Black or Custom Finishes. Opal 2 (Medium) or Opal 3 (Heavy) and 5133 or 5163 LED board required for full diffusion. Photometrics vary based on CCT and lensing; see vltcorp.com for conversion and other data specific to your fixture choices.

AVAILABLE IN LENGTHS UP TO 146.02" [3709MM]



ELL-7SL-

LED		CCT		Finish		Lens Options		Wire Exit		Listings & Options	
1720	260 lm/ft, 1.8 w/ft, 83 CRI	20	2000°K	AL	Silver Anodized	PG	Clear Acrylic	WE1	Default	UL	UL Listed
2730	397 lm/ft, 2.9 w/ft, 83 CRI	22	2200°K	BL	Black Anodized	L3	Lens 3 (42° - 44°)	C	Custom	CE	CE Marked (RoHS)
4740	528 lm/ft, 3.7 w/ft, 83 CRI	25	2500°K	C	Custom	L4	Lens 4 (65° - 76°)			MAG	Magnetic Mount
5760	665 lm/ft, 4.9w/ft, 83CRI	27	2700°K			OP1	Opal 1, Frosted				
6760	875 lm/ft, 6.5w/ft, 83 CRI	30	3000°K			OP2	Opal 2, Medium <sup>2</sup>				
3720	223 lm/ft, 1.8 w/ft, 95 CRI	35	3500°K			OP3	Opal 3, Heavy <sup>2</sup>				
3740	430 lm/ft, 3.5 w/ft, 95 CRI	40	4000°K								
3760	609 lm/ft, 5.2 w/ft, 95 CRI	45	4500°K								
3790	621 lm/ft, 6.9 w/ft, 98 CRI <sup>1</sup>	50	5000°K								
5133	315 lm/ft, 3.4w/ft, 87 CRI <sup>1</sup>										
5163	548 lm/ft, 6.6w/ft, 87 CRI <sup>1</sup>										

<sup>2</sup>Will provide full diffusion

**Fixture Length**  
See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]

Standard HI CRI Ultra HI CRI Pitchless

<sup>1</sup>Not Available in 20K, 22K or 25K CCT

### Fixture Accessories

ELL - AC - 7SL - MC	ELL - AC - 7SL - AMC	ELL - AC - S123 - AB	Factory Installed; See Options Above
<b>Fixed Metal Mounting Clip.</b> Fixture extrusion snaps into clip. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	<b>Adjustable Metal Mounting Clip.</b> Offset screws allow flush mounting. Bends to desired angle. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	<b>Adjustable Metal Bracket</b> for use with Fixed Metal Mounting Clip (one bracket per clip). 30° adjustability. Raises fixture 3/8" (9.52mm). Bracket allows repeated angle adjustments, and easier angle adjustments in hard-to-reach areas like ceiling coves. See Mounting Options.	<b>Magnetic Mount</b> Small, strong, factory installed magnets recess into rear side of fixture extrusions for mounting of fixture onto suitable ferrous surface or accessory Steel Mounting Plates; 3 magnets per foot. Magnets protrude 0.08" [2.1mm] above rear surface of extrusion.