


### New! 8LR CHOICE MEDIUM SQUARE EXTRUSION - EDGE TO EDGE LENS

8LR Choice: IP40 | Compact medium square extrusion for linear lighting applications. Slim extrusion wall (0.15") with 2 options of luminite lensing for seamless dot free imaging. UL Listed dry/damp. Includes selection of 8 LED Boards: 3 with Nichia LEDs on a Standard Pitch; 4 with EssentialLEDs Choice LEDs on a Narrow Pitch and 1 with Choice LEDs with Dim-to-Warm (3000°K to 1800°K) capability when used with Lutron driver. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. LF60 (Medium) or LF100 (Heavy) required for full diffusion. Photometrics vary based on CCT and lensing; see vltcorp.com for conversion and other data specific to your fixture choices.

AVAILABLE IN LENGTHS UP TO 95.46" [2425MM]



#### ELC- 8LR -

LED		Finish		Wire Exit		Listings & Options	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI <sup>2</sup>	AL	Silver Anodized	WE1	Default	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI <sup>2</sup>	BL	Black Anodized	C	Custom	CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI <sup>2</sup>					MAG	Magnetic Mount
4435	610 lm/ft, 5.8 w/ft, 90+ CRI <sup>2</sup>						
CCT		Lens Options		Fixture Length			
1320	222 lm/ft, 2.0 w/ft, 95+ CRI <sup>1</sup>	23	2300°K	LF60	Medium Diffusion	See Fixture Length and Wattage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]	
2320	335 lm/ft, 2.8 w/ft, 95+ CRI <sup>1</sup>	27	2700°K	LF100	Heavy Diffusion		
4320	590 lm/ft, 5.9 w/ft, 95+ CRI <sup>1</sup>	30	3000°K				
7435	455 lm/ft, 5.5 w/ft, 90+ CRI <sup>3</sup>	35	3500°K				
		40	4000°K				
		45	4500°K				
		18/30	1800°K/3000°K <sup>6</sup>				

<sup>1</sup> Not Available in 23K CCT  
<sup>2</sup> Not Available in 45K CCT  
<sup>3</sup> Requires a 5n1 or Lutron Driver

<sup>6</sup> 7435 Boards Only: CRI varies based on CCT combination

#### Fixture Accessories

ELL - AC - 8LR - MC	ELL - AC - 9SL - AMC	ELL - AC - S123 - AB	Factory Installed; See Options Above
<b>Fixed Metal Mounting Clip.</b> Fixture extrusion snaps into clip. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	<b>Adjustable Metal Mounting Clip.</b> Offset screws allow flush mounting. Bends to desired angle. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	<b>Adjustable Metal Bracket.</b> For use with Fixed Metal Mounting Clip (one bracket per clip). 30° adjustability. Raises fixture 3/8" (9.52mm). Bracket allows repeated angle adjustments, and easier angle adjustments in hard-to-reach areas like ceiling coves. See Mounting Options.	<b>Magnetic Mount.</b> Small, strong, factory installed magnets recess into rear side of fixture extrusions for mounting of fixture onto suitable ferrous surface or accessory Steel Mounting Plates (see Mounting Options); 3 magnets per foot.