


## 8SL CHOICE MEDIUM SQUARE EXTRUSION - EDGE TO EDGE LENS

8SL Choice: IP40 | Medium square extrusion for linear lighting applications. Slim extrusion wall (0.15") and edge-to-edge snap-in lensing for extra lumen output. UL Listed dry/damp. Includes selection of 8 LED Boards: 3 with Nichia LEDs on a Standard Pitch; 4 with EssentialLEDs Choice LEDs on a Narrow Pitch, and 1 with Choice LED's with Dim-to-Warm (3000°K to 1800°K) capability when used with a HELD-5n1 driver. See lumen outputs, CCTs, wattage and other variables on Choice Linear Fundamentals.

Available in Silver or Black Finishes. Choice of Clear Acrylic lens (standard), 3 Opal diffusion lenses, or three focusing lenses L2 (26° - 32°), L3 (50° - 51°) or L4 (89° - 92°).

AVAILABLE IN LENGTHS UP TO 143.3" [3640MM]



### ELC- 8SL -

LED		Finish		Wire Exit		Listings & Options	
1435	288 lm/ft, 2.7 w/ft, 90+ CRI <sup>2</sup>	AL	Silver Anodized	WE1	Default	UL	UL Listed
2435	384 lm/ft, 3.7 w/ft, 90+ CRI <sup>2</sup>	BL	Black Anodized	C	Custom	CE	CE Marked (RoHS)
3435	478 lm/ft, 5.5 w/ft, 90+ CRI <sup>2</sup>					MAG	Magnetic Mount
4435	610 lm/ft, 5.8 w/ft, 90+ CRI <sup>2</sup>						
1320	222 lm/ft, 2.0 w/ft, 95+ CRI <sup>1</sup>						
2320	335 lm/ft, 2.8 w/ft, 95+ CRI <sup>1</sup>						
4320	590 lm/ft, 5.9 w/ft, 95+ CRI <sup>1</sup>						
7435	455 lm/ft, 5.5w/ft, 90+ CRI <sup>5</sup>						
		CCT		Lens Options		Fixture Length	
		23	2300°K	PG	Clear Acrylic	See Fixture Length and Watage Table. Choose the correct Code number for the LED board and fixture length of your choice or specify Custom Length as follows: C (12.25") or C [311mm]	
		27	2700°K	L2	Lens 2 (26° - 32°)		
		30	3000°K	L3	Lens 3 (50° - 51°)		
		35	3500°K	L4	Lens 4 (89° - 92°)		
		40	4000°K	OP1	Opal 1, Frosted		
		45	4500°K	OP2	Opal 2, Medium <sup>3</sup>		
		18/30	1800°K/3000°K <sup>6</sup>	OP3	Opal 3, Heavy <sup>3, 4</sup>		

■ Narrow Pitch Choice LEDs  
■ Standard Pitch Nichia LEDs  
■ Dim-to Warm Choice LEDs

<sup>1</sup> Not Available in 23K CCT  
<sup>2</sup> Not Available in 45K CCT  
<sup>5</sup> Requires a HELD-5n1 Driver  
<sup>6</sup> 7435 Boards Only: CRI varies based on CCT combination  
<sup>3</sup> Will provide full diffusion  
<sup>4</sup> Not Title 24 JA8-2016 compliant

### Fixture Accessories

ELL - AC - 8SL - MC	ELL - AC - 8SL - AMC	ELL - AC - S123 - AB	Factory Installed; See Options Above
<b>Fixed Metal Mounting Clip.</b> Fixture extrusion snaps into clip. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	<b>Adjustable Metal Mounting Clip</b> Offset screws allow flush mounting. Bends to desired angle. Allow 1 per 12" (min. 2 per fixture). See Mounting Options.	<b>Adjustable Metal Bracket</b> for use with Fixed Metal Mounting Clip (one bracket per clip). 30° adjustability. Raises fixture 3/8" (9.52mm). Bracket allows repeated angle adjustments, and easier angle adjustments in hard-to-reach areas like ceiling coves. See Mounting Options.	<b>Magnetic Mount</b> Small, strong, factory installed magnets recess into rear side of fixture extrusions for mounting of fixture onto suitable ferrous surface or accessory Steel Mounting Plates. 3 magnets per foot. Magnets protrude 0.09" [2.3mm] above rear surface of extrusion.