
EssentialLEDs®

EFLEX INTERIOR FLEXIBLE ACCESSORIES

IP20 | Our EFlex Accessories allow you to build DIY LED fixtures on site with your choice of six different extrusion profiles. Extrusion and lensing can be purchased in 6 ft [1.83 m] lengths to be cut as needed; add end caps for easy custom-length fixtures with outstanding light

quality; all LEDs binned to within 2 Mac	Adam ellipse CCT, 95+ CRI.	
PROFILE 8SL	SPECIFICATIONS	CAT. NO. EFX - AC - 8SL - 6FT -
.51" [12.95mm]	Dimensions: 0.51"x 0.51" x 6 ft [12.95mm x 12.95mm x 1.83m] Material: Aluminum Finish: Silver (AL) or Black (BL)	Description: Profile 8SL aluminum extrusion in 6 ft [1.83 m] length; cut in field to desired lengths; combine with EFlex LED tape light to create DIY fixtures. Silver (AL) or Black (BL).
PROFILE 8CL	SPECIFICATIONS	CAT. NO. EFX - AC - 8CL - 6FT -
.51"[12.95mm]	Dimensions: 0.51"x 0.38" x 6 ft [12.95mm x 9.65mm x 1.83m] Material: Aluminum Finish: Silver (AL) or Black (BL)	Description: Profile 8CL aluminum extrusion in 6 ft [1.83 m] length; cut in field to desired lengths; combine with EFlex LED tape light to create DIY fixtures. Silver (AL) or Black (BL).
PROFILE 9SL	SPECIFICATIONS	CAT. NO. EFX - AC - 9SL - 6FT -
.94"[24.42mm]	Dimensions: 0.98"x 1.04" x 6 ft [24.89mm x 26.42mm x 1.83m] Material: Aluminum Finish: Silver (AL) or Black (BL)	Description: Profile 9SL aluminum extrusion in 6 ft [1.83 m] length; cut in field to desired lengths; combine with EFlex LED tape light to create DIY fixtures. Silver (AL) or Black (BL).
PROFILE 8FL	SPECIFICATIONS	CAT. NO. EFX- AC - 8FL - 6FT -
.76" [19.30mm] .030" .030" .0762mm] .51" [12.95mm]	Dimensions: 0.76" x 0.38" x 6ft [19.30mm x 9.65mm x 1.83m] Material: Aluminum Finish: Silver (AL) or Black (BL)	Description: Profile 8FL aluminum extrusion in 6 ft [1.83 m] length; cut in field to desired lengths; combine with EFlex LED tape light to create DIY fixtures. Silver (AL) or Black (BL).
PROFILE 2QL	SPECIFICATIONS	CAT. NO. EFX- AC - 2QL - 6FT -
.76" [19.30mm]	Dimensions: 1.02" x 0.76" x 6ft [25.91mm x 19.30mm x 1.83m] Material: Aluminum Finish: Silver (AL) or Black (BL)	Description: Profile 2QL aluminum extrusion in 6 ft [1.83 m] length; cut in field to desired lengths; combine with EFlex LED tape light to create DIY fixtures. Silver (AL) or Black (BL).
PROFILE 3RL	SPECIFICATIONS	CAT. NO. EFX - AC - 3RL - 6FT -
.65" [16.53mm]	Dimensions: 0.75" x 0.65" x 6ft [19.05mm x 16.53mm x 1.83m] Material: Aluminum Finish: Silver (AL) or Black (BL)	Description: Profile 3RL aluminum extrusion in 6 ft [1.83 m] length; cut in field to desired lengths; combine with EFlex LED tape light to create DIY fixtures Silver (AL) or Plack (PL)

page 84



tures. Silver (AL) or Black (BL).

CUT SHEET #9X105

EssentialLEDs®

PROFILE END CAP		SPECIFICATIONS	CAT. NO.
			85L 8CL 8FL 9SL 2QL 3RL
900	Material:	0.177" [4.5mm] Each Aluminum Silver (AL) or Black (BL)	Description: Aluminum End Cap for Profile extrusion. With Hole (HL) for wire exit end, Without Hole (NH) for non-wired end; one of each required to complete DIY fixture.
LENSING		SPECIFICATIONS	CAT. NO. EFX - AC - LENS
	Material:	6 ft [1.83m] Acrylic	PG OP1 OP2 OP3 Description: Lensing for all extrusion profiles in 6 ft [1.83m] length; cut in field to desired lengths for DIY fixtures. Lensing snaps securely into extru-
	Finish:	Clear, Frosted or Opal	sion.
CTARTER CARLE/COMMECTOR		CDECIFICATIONS	CAT NO FEW AC CU CC
STARTER CABLE/CONNECTOR		SPECIFICATIONS	CAT. NO. EFX - AC - CV- SC
		0.56" x 0.60" [15mm x 16mm], 8" [25.4mm] wire Plastic	Description: Easy, solderless connector for wiring EFlex DIY fixtures to driver; +/- prongs contact +/- solder points on EFlex tape; 8" of lead wire. Connector fits inside 9SL aluminum Profiles to create clean, finished linear fixture.
INTERCONNECT WIRE		SPECIFICATIONS	CAT. NO. EFX - AC - CV - ICW - 4
	Dimensions: Material:	0.56" x 0.60" [15mm x 16mm], 4" [101.6mm] wire Plastic	Description: 4" interconnect wire for daisy-chaining EFlex DIY fixtures together. Easy, solder-less connector on each end; +/- prongs contact +/- solder points on EFlex tape; connectors fit inside 9SL aluminum Profiles to create clean, finished linear fixture.
INTERCONNECT CONDUCTOR		SPECIFICATIONS	CAT. NO. EFX - AC - CV - ICC
		0.56" x 0.60" [15mm x 16mm] Plastic	Description: Plastic strip-to-strip gapless solderless conductor for making straight connection between two lengths of EFlex tape; +/- prongs snap down onto +/- solder points on EFlex tape to enable extended runs. Maximum run length 1320: 36' [1m], 2320: 26' [8m], 4320: 16.4' [5m]
MOUNTING CLIP			

Refer to Linear Mounting Accessories

page 85

