

CONSTANT CURRENT ELDOLED DRIVERS WITH JUNCTION BOX- 350/500/700/1050mA - DIMMABLE - 0-10V UL LISTED CLASS 2 POWER SUPPLIES

30W SOLOdrive DIMMABLE 0-10V W/ JUNCTION BOX



SPECIFICATIONS

Load: 30W Total
 Input Voltage: 120-277 V 50/60Hz
 Output Voltage: One Channel 2-55 V
 Dimensions: 9.70"L x 4.07"W x 2.93" H
 [247mm L x 103mm W x 75mm H]
 Weight: 38 oz. [1078 g]
 Max Ambient Temp.: 122° F [50° C]
 IP Rating: NEMA 3R
 Listings: UL Listed
 Driver Manufacturer: eldoLED
 Dimmable: Yes, 0-10V

CAT. NO. SL036151- -JB

Description: Single Channel
 Constant Current 30 watt LED
 Driver from EldoLED, Mounted
 in Junction Box for Hardwiring,
 Factory programmable output
 from 200mA to 1050mA; 30 VA load; 120
 – 277v 50/60Hz input; 2 – 55v Output 1
 Channel, 0 – 10v Dimmable, current sink
 or current source. Full Dimming from 100%
 to 0%, logarithmic dimming curve. NEMA
 3R case; Damp/Dry Rated. UL listed class
 2 power supply. For custom drive current,
 indicate mA rating between 200-1050 mA.

350
500
700
1050
CUST



50W SOLOdrive DIMMABLE 0-10V W/ JUNCTION BOX



SPECIFICATIONS

Load: 50W Total
 Input Voltage: 120-277 V 50/60Hz
 Output Voltage: Dual Channel 2-55 V each
 Dimensions: 9.70"L x 4.07"W x 2.93" H
 [247mm L x 103mm W x 75mm H]
 Weight: 40 oz. [1133 g]
 Max Ambient Temp.: 122° F [50° C]
 IP Rating: NEMA 3R
 Listings: UL Listed
 Driver Manufacturer: eldoLED
 Dimmable: Yes, 0-10V

CAT. NO. SL056151- -JB

Description: Dual Channel
 Constant Current 50 watt LED
 Driver from EldoLED, Mounted
 in Junction Box for Hardwiring,
 Factory programmable output
 from 200mA to 1050mA; 50 VA load; 120
 – 277v 50/60Hz input; 2 – 55v Output 2
 Channels, 0 – 10v Dimmable, current sink
 or current source. Full Dimming from 100%
 to 0%, logarithmic dimming curve. NEMA
 3R case; Damp/Dry Rated. UL listed class
 2 power supply. For custom drive current,
 indicate mA rating between 200-1050 mA.

350
500
700
1050
CUST



100W SOLOdrive DIMMABLE 0-10V W JUNCTION BOX



SPECIFICATIONS

Load: 100W Total
 Input Voltage: 120-277 V 50/60Hz
 Output Voltage: Quad Channel 2-55 V each
 Dimensions: 13.60"L x 4.07"W x 2.93" H
 [346mm L x 103mm W x 75mm H]
 Weight: 64 oz. [1814 g]
 Max Ambient Temp.: 122° F [50° C]
 IP Rating: NEMA 3R
 Listings: UL Listed
 Driver Manufacturer: eldoLED
 Dimmable: Yes, 0-10V

CAT. NO. SL106151- -JB

Description: Quad Channel
 Constant Current 100 watt LED
 Driver from EldoLED, Mounted
 in Junction Box for Hardwiring,
 Factory programmable output
 from 200mA to 1050mA; 100 VA load; 120
 – 277v 50/60Hz input; 2 – 55v Output 4
 Channels, 0 – 10v Dimmable, current sink
 or current source. Full Dimming from 100%
 to 0%, logarithmic dimming curve. NEMA
 3R case; Damp/Dry Rated. UL listed class
 2 power supply. For custom drive current,
 indicate mA rating between 200-1050 mA.

350
500
700
1050
CUST

