



CONSTANT CURRENT ELDOLED DRIVERS WITH JUNCTION BOX- 350/500/700/1050mA - DIMMABLE - DALI UL LISTED CLASS 2 POWER SUPPLIES

50W SOLOdrive DIMMABLE DALI W/ JUNCTION BOX	SPECIFICATIONS	CAT. NO.	SL0560S2-	-JB
	<p>Load: 50W Total Input Voltage: 120-277 V 50/60Hz Output Voltage: Three Channel 2-55 V each Dimensions: 9.70"L x 4.07"W x 2.93" H [247mm L x 103mm W x 75mm H] Weight: 40 oz. [1133 g] Max Ambient Temp.: 122° F [50° C] IP Rating: NEMA 3R Listings: UL Listed Driver Manufacturer: eldoLED Dimmable: Yes, DALI</p>	<p>Description: Two Channel Constant Current 50 watt LED Driver from EldoLED, Mounted in Junction Box for Hardwiring, Factory programmable output from 200mA to 1050mA; 50VA load; 120-277v 50/60Hz input; 2 - 55v Output 2 Channels, DALI Dimmable. Full Dimming from 100% to 0%, logarithmic, linear or square dimming curve. 2 low voltage leads for DALI Input/Output. NEMA 3R case; Damp/Dry Rated. UL listed class 2 power supply. For custom drive current, indicate mA rating between 200-1050 mA.</p>	350	
			500	
			700	
			1050	
			CUST	



100W SOLOdrive DIMMABLE DALI W JUNCTION BOX	SPECIFICATIONS	CAT. NO.	SL1060S1-	-JB
	<p>Load: 100W Total Input Voltage: 120-277 V 50/60Hz Output Voltage: Quad Channel 2-57 V each Dimensions: 13.60"L x 4.07"W x 2.93" H [346mm L x 103mm W x 75mm H] Weight: 64 oz. [1814 g] Max Ambient Temp.: 122° F [50° C] IP Rating: NEMA 3R Listings: UL Listed Driver Manufacturer: eldoLED Dimmable: Yes, DALI</p>	<p>Description: Quad Channel Constant Current 100 watt LED Driver from EldoLED, Mounted in Junction Box for Hardwiring, Factory programmable output from 200mA to 1050mA; 100 VA load; 120 - 277v 50/60Hz input; 4 - 57v Output 4 Channels, DMX Dimmable. Full Dimming from 100% to 0%, logarithmic or linear dimming curve. 2 low voltage leads for DALI Input/Output. NEMA 3R case; Damp/Dry Rated. UL listed class 2 power supply. For custom drive current, indicate mA rating between 200-1050 mA.</p>	350	
			500	
			700	
			1050	
			CUST	

