












VLT HYBRID ELECTRONIC LINEAR DRIVERS, 24V DC WITH ELDOLED DALI DIMMING MODULE

VLT Hybrid Electronic Linear Drivers with DALI Dimming Module (HELD-DALI) feature solid state drive circuits that will produce maximum voltage not greater than 24.3v DC; DALI dimmable and fully potted to dim without humming or buzzing. Two surface mount RJ45 Connectors for DALI IN/ DALI OUT; UL and CE Listed (UL 1012, UL1013 & UL 8750). VLT HELD-DALI drivers come complete with knock-outs and mounting brackets for easy installation, dry location. Manufactured in Southern California.

ALL DRIVERS are UL Listed (UL 1012, UL 1310, UL 8750)
See dimmer compatibility chart on page 137 for approved Lutron Dimmers

48W 24V DC DALI	SPECIFICATIONS	CAT. NO.	HELD -	- 48 - 24DC -		
	Load: 1-48 VA Input Voltage: 120/240/277 Output Voltage: 24v DC ±1% In Rush: Soft Start Dimensions: 11.5" L x 5.75" W x 1.87" H [292mm L x 146mm W x 47.5mm H] DALI Channels: 1 or 2 Channels Circuits: 1 or 2 Circuits Frequency: 50/60Hz Weight: 2.5 lbs. [1.13 kg] Max Ambient Temp.: 140° F [60° C] IP Rating: IP20 Listings: UL, CE Listed (UL1012, UL1310, UL 8750) Manufacturer: Visual Lighting Technologies	DALI1 DALI2	- 120 240/277	- UL CE	 	Made in USA 
	Load: 1-72 VA Input Voltage: 120/240/277 Output Voltage: 24v DC ±1% In Rush: Soft Start Dimensions: 11.5" L x 5.75" W x 1.87" H [292mm L x 146mm W x 47.5mm H] DALI Channels: 1 or 2 Channels Circuits: 1 or 2 Circuits Frequency: 50/60Hz Weight: 2.5 lbs. [1.13 kg] Max Ambient Temp.: 140° F [60° C] IP Rating: IP20 Listings: UL, CE Listed (UL1012, UL1310, UL 8750) Manufacturer: Visual Lighting Technologies	DALI1 DALI2	- 120 240/277	- UL CE	 	Made in USA 
	Load: 1-96 VA Input Voltage: 120/240/277 Output Voltage: 24v DC ±1% In Rush: Soft Start Dimensions: 11.5" L x 5.75" W x 1.87" H [292mm L x 146mm W x 47.5mm H] DALI Channels: 1 or 2 Channels Circuits: 1 or 2 Circuits Frequency: 50/60Hz Weight: 2.5 lbs. [1.13 kg] Max Ambient Temp.: 140° F [60° C] IP Rating: IP20 Listings: UL, CE Listed (UL1012, UL1310, UL 8750) Manufacturer: Visual Lighting Technologies	DALI1 DALI2	- 120 240/277	- UL CE	 	Made in USA 