




VLT HYBRID ELECTRONIC LINEAR DRIVERS, 24V DC WITH ELDOLED DMX DIMMING MODULE




VLT Hybrid Electronic Linear Drivers with DMX Dimming Module (HELD-DMX) feature **solid state drive circuits** that will produce maximum voltage not greater than 24.3v DC; DMX dimmable and fully potted to dim without humming or buzzing. Two surface mount RJ45 Connectors for DMX IN/ DMX OUT; UL & CE Listed (UL 1012, UL1013 & UL 8750). VLT HELD-DMX drivers come complete with knock-outs and mounting brackets for easy installation, dry location. Manufactured in Southern California.

ALL DRIVERS are UL Listed (UL 1012, UL 1310, UL 8750)



See dimmer compatibility chart on page 137 for approved Lutron Dimmers

48W 24V DC DMX	SPECIFICATIONS	CAT. NO.	HELD -	- 48 - 24DC -	
	Load: 1-48 VA Input Voltage: 120/240/277 Output Voltage: 24v DC ±1% In Rush: Soft Start Dimensions: 11.5" L x 5.75" W x 1.87" H [292mm L x 146mm W x 47.5mm H] DMX Channels: 1 or 2 Channels Circuits: 1 or 2 Circuits Connectors: Neutrik Ethercon Frequency: 50/60Hz Weight: 2.5 lbs. [1.13 kg] Max Ambient Temp.: 140° F [60° C] IP Rating: IP20 Listings: UL, CE Listed (UL1012, UL1310, UL 8750) Manufacturer: Visual Lighting Technologies				
		DMX1		120	UL
		DMX2		240/277	CE
		Description: Constant voltage driver from VLT, 24v DC, 48w, 2 amps; fully dimmable with built in eldoLED DMX Dimming Module; 1 channel or 2 channels; soft start "no in rush"; 120VAC - 277VAC input; 24VDC output (meets Class 2 output limits). Conduit access wiring compartment for wall mounting; two surface mount Neutrik Ethercon (RJ45) Connectors for DMX IN/ DMX OUT; UL Listed. NEMA 3R case; Indoor rated.			
				Made in USA 	



72W 24V DC DMX	SPECIFICATIONS	CAT. NO.	HELD -	- 72 - 24DC -	
	Load: 1-72 VA Input Voltage: 120/240/277 Output Voltage: 24v DC ±1% In Rush: Soft Start Dimensions: 11.5" L x 5.75" W x 1.87" H [292mm L x 146mm W x 47.5mm H] DMX Channels: 1 or 2 Channels Circuits: 1 or 2 Circuits Connectors: Neutrik Ethercon Frequency: 50/60Hz Weight: 2.5 lbs. [1.13 kg] Max Ambient Temp.: 140° F [60° C] IP Rating: IP20 Listings: UL, CE Listed (UL1012, UL1310, UL 8750) Manufacturer: Visual Lighting Technologies				
		DMX1		120	UL
		DMX2		240/277	CE
		Description: Constant voltage driver from VLT, 24v DC, 72w, 3 amps; fully dimmable with built in eldoLED DMX Dimming Module; 1 channel or 2 channels; soft start "no in rush"; 120VAC - 277VAC input; 24VDC output (meets Class 2 output limits). Conduit access wiring compartment for wall mounting; two surface mount Neutrik Ethercon (RJ45) Connectors for DMX IN/ DMX OUT; UL Listed. NEMA 3R case; Indoor rated.			
				Made in USA 	



96W 24V DC DMX	SPECIFICATIONS	CAT. NO.	HELD -	- 96 - 24DC -	
	Load: 1-96 VA Input Voltage: 120/240/277 Output Voltage: 24v DC ±1% In Rush: Soft Start Dimensions: 11.5" L x 5.75" W x 1.87" H [292mm L x 146mm W x 47.5mm H] DMX Channels: 1 or 2 Channels Circuits: 1 or 2 Circuits Connectors: Neutrik Ethercon Frequency: 50/60Hz Weight: 2.5 lbs. [1.13 kg] Max Ambient Temp.: 140° F [60° C] IP Rating: IP20 Listings: UL, CE Listed (UL1012, UL1310, UL 8750) Manufacturer: Visual Lighting Technologies				
		DMX1		120	UL
		DMX2		240/277	CE
		Description: Constant voltage driver from VLT, 24v DC, 96w, 4 amps; fully dimmable with built in eldoLED DMX Dimming Module; 1 channel or 2 channels; soft start "no in rush"; 120VAC - 277VAC input; 24VDC output (meets Class 2 output limits). Conduit access wiring compartment for wall mounting; two surface mount Neutrik Ethercon (RJ45) Connectors for DMX IN/ DMX OUT; UL Listed. NEMA 3R case; Indoor rated.			
				Made in USA 