

VLT HYBRID ELECTRONIC LINEAR DRIVERS

VLT Electronic Switching Drivers feature **solid state drive circuits** that will produce maximum voltage not greater than 24.3v DC; fully dimmable. **VLT HELD** drivers are UL Listed (UL 1012, UL1013 & UL8750). They come complete with knock-outs and mounting brackets for easy installation. Manufactured in Southern California.

ALL DRIVERS are ETL Listed (UL 2108, UL 8750), when used as part of an EssentialLEDs Linear or EssentialLEDs Light Panel system.
See dimmer compatibility chart for approved Lutron Dimmers

48W 24V DC	SPECIFICATIONS	CAT. NO.	HELD - 48 - 24DC -
			120 240/277



Load: 1-48 VA
 Input Voltage: 120/240/277
 Output Voltage: 24v DC ±1%
 Dimensions: 13.75"L x 2.37"W x 1.25"H
 [349mm L x 60.2mm W x 31.8mm]
 Circuits: 1
 Frequency: 50/60Hz
 Weight: 1.5 lbs (0.7 kg)
 Max Ambient Temp.: 140° F [60° C]
 IP Rating: IP65
 Listings: UL Listed (UL1012, UL1310, UL 8750)
 Manufacturer: Visual Lighting Technologies

Description: Constant voltage driver from VLT, 48w, 2A; dimmable; 120VAC - 277VAC input; 24VDC output (meets Class 2 output limits). Conduit access wiring compartment for wall mounting; UL Listed. A NEMA 3R case; indoor/outdoor rated (non-submersible).



Made in USA

96W 24V DC	SPECIFICATIONS	CAT. NO.	HELD - 96 - 24DC -
			120 240/277



Load: 1-96 VA
 Input Voltage: 120/240/277
 Output Voltage: 24v DC ±1%
 Dimensions: 13.75"L x 2.37"W x 1.25"H
 [349mm L x 60.2mm W x 31.8mm]
 Circuits: 1
 Frequency: 50/60Hz
 Weight: 1.5 lbs (0.7 kg)
 Max Ambient Temp.: 140° F [60° C]
 IP Rating: IP65
 Listings: UL Listed (UL1012, UL1310, UL 8750)
 Manufacturer: Visual Lighting Technologies

Description: Constant voltage driver from VLT, 96w, 4A; dimmable; 120VAC - 277VAC input; 24VDC output (meets Class 2 output limits). Conduit access wiring compartment for wall mounting; UL Listed. NEMA 3R case; indoor/outdoor rated (non-submersible).



Made in USA

288W 24V DC	SPECIFICATIONS	CAT. NO.	HELD - 288 - 24DC -
			120 240/277



Load: 1-96 VA
 Input Voltage: 120/240/277
 Output Voltage: 24v DC ±1%
 Dimensions: 11.5"L x 5.75"W x 1.87"H
 [292mm L x 146mm W x 47.5mm]
 Circuits: 3
 Frequency: 50/60Hz
 Weight: 2.5 lbs (0.7 kg)
 Max Ambient Temp.: 140° F [60° C]
 IP Rating: IP20
 Listings: UL Listed (UL1012, UL1310),
 Manufacturer: Visual Lighting Technologies

Description: Constant voltage driver from VLT, 288w, 4A; dimmable; 120VAC - 277VAC input; 24VDC output 96w each (meets Class 2 output limits). Conduit access wiring compartment for wall mounting; UL Listed. NEMA 3R case; indoor rated.



Made in USA