








LUTRON DRIVERS, 24V DC FOR USE WITH EcoSYSTEM CONTROLS, 3-WIRE & 2-WIRE

Lutron constant voltage drivers for use with Lutron EcoSystem Controls and 3-wire and 2-wire systems; smooth, flicker-free continuous dimming; 120-277 VAC input; UL Listed, RoHS compliant. Compatible with multiple controls systems, see below.

40W24V DC (ECO-SYSTEM OR 3-WIRE)	SPECIFICATIONS	CAT. NO.	L3DA4U1UKL- CV240
	Load: 1-40 VA Input Voltage: 120 /277 Output Voltage: 24v DC In Rush Current: <2 A Dimensions: Driver case: 3" x 1" x 4.9" [76mm x 25mm x 124mm] J-Box: 4" x 1.5" x 4" [102mm x 38mm x 102mm] Frequency: 50/60Hz Weight: 1.65 lbs. [0.75kg] Max Ambient Temp.: 149°F [65° C] IP Rating: IP20 Listings: UL 8750 Manufacturer: Lutron	<p>Description: Constant Voltage Hi-Lume driver from Lutron, 40w, 24VDC; smooth, flicker-free continuous dimming from 100% to 1%; for use with Lutron EcoSystem Controls & 3-wire systems; 120-277 VAC input; UL Listed; RoHS compliant. 16 knockout options.</p> <p>K-case mounted on 4" x 1.5" x 4" [102mm x 38mm x 102mm] J-Box with UL Listed wiring compartment.</p> <p>Compatible with Energi Savr Node™ units with EcoSystem™, GRAFIK Eye® QS control unit, PowPak® dimming module with EcoSystem™, and Quantum® systems, allowing for integration into a planned or existing EcoSystem™ lighting control solution.</p>	 

40W24V DC (2-WIRE)	SPECIFICATIONS	CAT. NO.	LTEA4U1UKL-CV240
	Load: 1-40 VA Input Voltage: 120 /277 Output Voltage: 24v DC In Rush Current: <2 A Dimensions: Driver case: 3" x 1" x 4.9" [76mm x 25mm x 124mm] J-Box: 4" x 1.5" x 4" [102mm x 38mm x 102mm] Frequency: 50/60Hz Weight: 1.65 lbs. [0.75kg] Max Ambient Temp.: 149°F [65° C] IP Rating: IP20 Listings: UL 8750 Manufacturer: Lutron	<p>Description: Constant Voltage Hi-Lume driver from Lutron, 40w, 24VDC; smooth, flicker-free continuous dimming from 100% to 1%; for use with 2-wire systems; 120-277 VAC input; UL Listed; RoHS compliant. 16 knockout options.</p> <p>K-case mounted on 4" x 1.5" x 4" [102mm x 38mm x 102mm] J-Box with UL Listed wiring compartment.</p> <p>Compatible with Energi Savr Node™ units with EcoSystem™, GRAFIK Eye® QS control unit, PowPak® dimming module with EcoSystem™, and Quantum® systems, allowing for integration into a planned or existing EcoSystem™ lighting control solution.</p>	 

96W24V DC (ECO-SYSTEM or 3-WIRE)	SPECIFICATIONS	CAT. NO.	L3D0-96W-24V-U
	Load: 1 - 96 VA Input Voltage: 120/277 Output Voltage: 24v DC In Rush Current: <2 A Dimensions: 5.5" x 2.0" x 10.5" [140mm x 51mm x 267mm] Frequency: 50/60Hz Weight: 3.60 lbs. [1.632 kg] Max Ambient Temp.: 104°F [40° C] IP Rating: IP20 Listings: UL 8750/CSA C22.2 No. 250.13-14 RoHS Compliant Manufacturer: Lutron	<p>Description: Constant Voltage Hi-Lume Premier driver from Lutron, 96w, 24VDC; smooth, flicker-free continuous dimming from 100% to 0.1%; Soft-on, Fade-to-Black operation for EcoSystem Controls; for use with Lutron EcoSystem Controls & 3-wire systems; field adjustment knob offers low-end light output tuning; 120-277 VAC input; UL Listed; RoHS compliant.</p> <p>Guaranteed dimming performance when used with HomeWorks®QS, Energi Savr Node™ units with EcoSystem™, GRAFIK Eye® QS with EcoSystem™, and Quantum® systems, allowing for integration into a planned or existing EcoSystem™ lighting control solution.</p>	