

## ELECTRONIC DRIVERS FROM MAGNITUDE

### 96W 24V DC - DIMMING DRIVER

#### SPECIFICATIONS

CAT. NO. CVD96L24DC



Load: 1-96VA  
 Input Voltage: 120-277V 50/60Hz  
 Output Voltage: 24V DC  $\pm 1\%$   
 Dimensions: 12.1"L x 2.36"W x 1.4"H  
 [307.9mm L x 59.9mm W x 35mm H]  
 Weight: 30.95 oz. [878 g]  
 Max Ambient Temp.: 104° F [40°C]  
 IP Rating: 65 (Damp)  
 Listings: UL Listed  
 Manufacturer: Magnitude

**Description:** Constant voltage 96 watt 24 volt driver from Magnitude; 1-96VA load, 120v-277v 50/60Hz input; 24V output DC;  $\pm 1\%$ ; driver with self-contained 0-10v dimming capability. Control device required. Damp rated.



### 60W 24V DC - DIMMING DRIVER

#### SPECIFICATIONS

CAT. NO. CVD60L24DC



Load: 1-60VA  
 Input Voltage: 120-277V 50/60Hz  
 Output Voltage: 24V DC  $\pm 1\%$   
 Dimensions: 12.1"L x 2.36"W x 1.4"H  
 [307.9mm L x 59.9mm W x 35mm H]  
 Weight: 30.95 oz. [878 g]  
 Max Ambient Temp.: 104° F [40°C]  
 IP Rating: 65 (Damp)  
 Listings: UL Listed  
 Manufacturer: Magnitude

**Description:** Constant voltage 60 watt 24 volt driver from Magnitude; 1-60VA load, 120v-277v 50/60Hz input; 24V output DC;  $\pm 1\%$ ; driver with self-contained 0-10v dimming capability. Control device required. Damp rated.



### 30W 24V DC - DIMMING DRIVER

#### SPECIFICATIONS

CAT. NO. CVD30L24DC



Load: 1-30VA  
 Input Voltage: 120-277V 50/60Hz  
 Output Voltage: 24V DC  $\pm 1\%$   
 Dimensions: 12.1"L x 2.36"W x 1.4"H  
 [307.9mm L x 59.9mm W x 35mm H]  
 Weight: 30.95 oz. [878 g]  
 Max Ambient Temp.: 104° F [40°C]  
 IP Rating: 65 (Damp)  
 Listings: UL Listed  
 Manufacturer: Magnitude

**Description:** Constant voltage 30 watt 24 volt driver from Magnitude; 1-30VA load, 120v-277v 50/60Hz input; 24V output DC;  $\pm 1\%$ ; driver with self-contained 0-10v dimming capability. Control device required. Damp rated.

