EssentialLEDs[®]

MINI DESIGNER EXTRUSION - NO LENS

IP20 | Mini Rounded Designer extrusion for linear lighting applications. Includes Nichia LEDs in choice of 11 LED Board options. See lumen outputs, CCTs, wattage and other variables on Linear Fundamentals.

Available in Silver, Black or Bronze Anodized, White Powder Coated or Custom Finishes. Photometrics vary based on CCT; see linear fundamentals for conversion and other data specific to your fixture.

27

35

40

3000°K


3500°K

4000°K

4500°K

5000°K





OBSERVE PRECAUTIONS SENSITIVE DEVICES

ELL- ML1											 		
	T		Ī			Ī	ı	•		1		Ţ	
					Finish			Wire Exit		Li	stings & Options		
1720	260 lm/ft, 1.8 w/ft, 83 CRI				AL	Silver Anodized			WE1	Default	UL	UL Listed	c (UL) us
2730	397 lm/ft, 2.9 w/ft, 83 CRI				BL	Black Anodized				-	CE	CE Listed (Ro	HS) (E
4740	528 lm/ft, 3.7 w/ft, 83 CRI				ВZ	Bronze Anodized				Fixture Length	MAG	Magnetic Mo	ount
5760	665 lm/ft, 4.9w/ft, 83CRI		CCT	١	WH	White Powder Coat	Lens	Options	-	See Fixture Length & Wattage		1	
6760	875 lm/ft, 6.5w/ft, 83 CRI	20	2000°K		C	Custom		o Lens		Table; choose the correct Code number for the LED board and			
3720	223 lm/ft, 1.8 w/ft, 95 CRI	22	2200°K			•				fixture length of your choice			
3740	430 lm/ft, 3.5w/ft, 95 CRI	25	2500°K							or specify Custom Length as follows: C (12.25") C [311mm]			

follows: C (12.25") C [311mm] 2700°K

¹Not Available in 20K, 22K or 25K CCT

Standard Ultra HI CRI

3790

HI CRI

609 lm/ft, 5.2 w/ft, 95 CRI

621 lm/ft, 6.9 w/ft, 98 CRI¹

315 lm/ft, 3.4 w/ft, 87 CRI¹

5163 548 lm/ft, 6.6 w/ft, 87 CRI¹

Pitchless

Fixture Accessories ELL - AC - MLR - MC Factory Installed; See Options Above Magnet Adds 0.08" [2.1mm] to height 0.384" [9.760mm] 0.35 [9.0mm]

page 22

Description: Fixed Metal Clip for mounting ML1 extrusion. Screws to mounting surface with screw, provided. Fixture snaps into clip. Allow 1 per 12" of extrusion (min. 2 per fixture).

Description: Magnetic Mount for ML1 extrusion. Small, strong magnets recess into rear side of fixture extrusions for magnetic mounting of fixture on suitable surface. Factory installed. Adds 0.08" [2.1mm] to fixture height.