

NASSAU SERIES

Fiber Optic Steplight Fixtures



- Recessed telescopic accent light
- Versatile 90° Vertical adjustment, 110° Horizontal rotation
- · Tool-less locking adjustment
- · Simple, discrete profile when recessed
- · Multiple lens options and variable beam angles
- · Glare-free lens
- · Wonderful flexibility for galleries and displays

FIBER OPTIC LIGHTING

Nassau Series - Fiber Optic Steplight Fixtures

2.5mm [.098] 15.0mm [.591]

Specifications

CAT. NO. NS - SH - AST - 21 - NL -

AL BL ΒZ

WH

Fiber Type: PMMA or Glass

Fiber Sizes: 1.0mm, 1.5mm, 2.0mm, 3.0mm,

Ferrule Type: Shelf Ferrule Fixture Size: 21mm Lens Type: No Lens

Beam Angle: 54°, Tilted Down 30° Mounting: Recessed, Tension Clip

Primary Material: Aluminum


Description:

Nassau Series (Roblon Asymetric Fitting 30°) steplight fixture with no lens and 21mm outer diameter; asymmetrical beam spread for illuminating horizontal plane of steps; accepts PMMA or glass fiber up to 3.0mm; recessed mounting with tension clips into side of staircase; multiple finishes available.

Finishes Available:

Silver (AL), Black (BL), Bronze (BZ), White (WH)

Specifications



Fiber Type: PMMA or Glass

Fiber Sizes: 1.0mm, 1.5mm, 2.0mm,

3.0mm, 4.5mm

Ferrule Type: Indoor Ferrule

Fixture Size: 31mm

Lens Type: Plain Flat Glass Lens Beam Angle: 54°, Tilted Down 30° Mounting: Recessed, Conduit

Primary Material: Stainless Steel 316

Description:

Nassau Series (Roblon Sirius Angle) steplight fixture with plain flat glass lens and 31mm outer diameter; asymmetrical beam spread for illuminating horizontal plane of steps; accepts PMMA or glass fiber up to 4.5mm; recessed mounting into 22mm conduit at side of staircase; stainless steel finish.

Finishes Available:

Stainless Steel (SS) - Marine Grade 316, Outdoor

IP44 Rated

Specifications

CAT. NO. NS - ID - ST - 29 - NL -

CAT. NO. NS - ID - AST - 31 - PG - SS

ΑL BL

Fiber Type: PMMA or Glass

4.5mm, 6.0mm

Fiber Sizes: 1.0mm, 1.5mm, 2.0mm, 3.0mm,

Ferrule Type: Indoor Ferrule

Fixture Size: 29mm Lens Type: No Lens Beam Angle: Diffuse

Mounting: Semi-recessed, Tension Clip


Primary Material: Aluminum

Description:

Nassau Series (Roblon Staircase Fitting) stair riser steplight fixture with glare shield, no lens and 29mm outer diameter; accepts PMMA or glass fiber up to 6.0mm; semi-recessed with tension clips on vertical plane of steps to illuminate horizontal stair tread; multiple finishes available.

Finishes Available:

Silver (AL), Black (BL), Bronze (BZ)



10.0mm [.394]